



UTILITY PATENT APPLICATION TRANSMITTAL

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No.

862.C2036

First Named Inventor or Application Identifier

Koji NAKAGIRI

Express Mail Label No.

USPTO
09/703684

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

ADDRESS TO:

Commissioner for Patents
Box Patent Application
Washington, DC 20231

1. ☐ Fee Transmittal Form
(Submit an original, and a duplicate for fee processing)
2. ☐ Applicant claims small entity status.
See 37 CFR 1.27.
3. ☒ Specification Total Pages
4. ☒ Drawing(s) (35 USC 113) Total Sheets
5. ☐ Oath or Declaration Total Pages
- a. ☐ Newly executed (original or copy)
- b. ☐ Copy from a prior application (37 CFR 1.63(d))
(for continuation/divisional with Box 17 completed)
- i. ☐ **DELETION OF INVENTOR(S)**
Signed Statement attached deleting inventor(s)
named in the prior application, see 37 CFR
1.63(d)(2) and 1.33(b)
6. ☒ Application Data Sheet. See 37 CFR 1.76

7. ☐ CD-ROM or CD-R in duplicate, large table or Computer
Program (Appendix)
8. ☐ Nucleotide and/or Amino Acid Sequence Submission
(if applicable, all necessary)
- a. ☐ Computer Readable Form (CRF)
- b. Specification Sequence Listing on:
- i. ☐ CD-ROM or CD-R (2 copies); or
- ii. ☐ paper
- c. ☐ Statements verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

9. ☐ Assignment Papers (cover sheet & document(s))
10. ☐ 37 CFR 3.73(b) Statement ☐ Power of Attorney
(when there is an assignee)
11. ☐ English Translation Document (if applicable)
12. ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS
Citations
13. ☐ Preliminary Amendment
14. ☒ Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)
15. ☐ Certified Copy of Priority Document(s)
(if foreign priority is claimed)
16. ☐ Other: _____

17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. ____/____
Prior application information: Examiner _____ Group/Art Unit: _____

For CONTINUATION OR DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts

18 CORRESPONDENCE ADDRESS

☒ Customer Number or Bar Code Label 05514
(Insert Customer No. or Attach bar code label here) or ☐ Correspondence address below

NAME				
Address				
City	State	Zip Code		
Country	Telephone	Fax		



CLAIMS	(1) FOR	(2) NUMBER FILED	(3) NUMBER EXTRA	(4) RATE	(5) CALCULATIONS
	TOTAL CLAIMS (37 CFR 1.16(c))	18-20 =	0	X \$ 18.00 =	\$0
	INDEPENDENT CLAIMS (37 CFR 1.16(b))	3-3 =	0	X \$ 80.00 =	\$0
	MULTIPLE DEPENDENT CLAIMS (if applicable) (37 CFR 1.16(d))			\$270.00 =	\$0
				BASIC FEE (37 CFR 1.16(a))	\$710.00
			Total of above Calculations =		\$710.00
	Reduction by 50% for filing by small entity (Note 37 CFR 1.9, 1.27, 1.28).				0
	TOTAL =				\$710.00

19. Small entity status


- a. ☐ A small entity statement is enclosed
- b. ☐ A small entity statement was filed in the prior nonprovisional application and such status is still proper and desired.
- c. ☐ Is no longer claimed.

20. ☒ A check in the amount of \$ 710.00 to cover the filing fee is enclosed.

21. ☐ A check in the amount of \$ _____ to cover the recordal fee is enclosed.

22. The Commissioner is hereby authorized to credit overpayments or charge the following fees to Deposit Account No. 06-1205:

- a. ☒ Fees required under 37 CFR 1.16.
- b. ☒ Fees required under 37 CFR 1.17.
- c. ☐ Fees required under 37 CFR 1.18.

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT REQUIRED	
NAME	LEONARD P. DIANA (Reg. No. 29,296)
SIGNATURE	
DATE	November 1, 2000

INVENTOR INFORMATION

Inventor One Given Name:: Koji
Family Name:: NAKAGIRI
Postal Address Line One:: c/o Canon Kabushiki Kaisha,
Postal Address Line Two:: 30-2, Shimomaruko 3-chome,
City:: Ohta-ku
State or Province:: Tokyo
Country:: JAPAN
Inventor Two Given Name:: Satoshi
Family Name:: NISHIKAWA
Postal Address Line One:: c/o Canon Kabushiki Kaisha,
Postal Address Line Two:: 30-2, Shimomaruko 3-chome,
City:: Ohta-ku
State or Province:: Tokyo
Country:: JAPAN
Inventor Three Given Name:: Yasuo
Family Name:: MORI
Postal Address Line One:: c/o Canon Kabushiki Kaisha,
Postal Address Line Two:: 30-2, Shimomaruko 3-chome,
City:: Ohta-ku
State or Province:: Tokyo
Country:: JAPAN

CORRESPONDENCE INFORMATION

Correspondence Customer Number:: 05514
Fax:: (212) 218-2200

APPLICATION INFORMATION

Title Line One:: PRINT CONTROL METHOD AND APPARATUS
Total Drawing Sheets:: 29
Formal Drawings?: Yes
Application Type:: Utility
Docket Number:: 862.C2036
Secrecy Order in Parent Appl.?: No

REPRESENTATIVE INFORMATION

Representative Customer Number:: 5514

PRIOR FOREIGN APPLICATIONS

Foreign Application One:: 11-313118

Filing Date:: 11-02-1999

Country:: JAPAN

Priority Claimed:: Yes

TITLE OF THE INVENTION
PRINT CONTROL METHOD AND APPARATUS

FIELD OF THE INVENTION

5 The present invention relates to a print control method, apparatus, and a computer program for controlling the apparatus and, more particularly, to a print control method and apparatus in a system including an information processing apparatus such as a
10 personal computer or the like, and a printer.

BACKGROUND OF THE INVENTION

 Upon printing data such as text data, image data, or the like edited by an application program for
15 editing text or image data, a print preview function that presents an image to be printed on the screen in a print layout to the user before the image is actually printed on a paper sheet is known. The print preview function is included in the application program, and
20 has only a function of displaying a preview image.

 The user checks an image to be printed exploiting this print preview function, and can re-edit it by the application program until an ideal layout is realized.

 However, the print preview function provided by
25 the application program cannot display, as a preview image, an image which reflects various print conditions

that a printer driver can set. Also, the user must set the size or the like of a preview image in accordance with the screen size, resulting in troublesome operation. For example, even when the user wants to
5 simultaneously display preview images for several pages, the application program displays them with an arbitrary size and layout in response to a preview display instruction. For this reason, the user must re-set the size and layout after display. Even when the user
10 re-sets them, a preview image is not always displayed according to that layout in which the image is to be printed.

SUMMARY OF THE INVENTION

15 The present invention has been made in consideration of the aforementioned prior art, and has as its object to provide a print control method and apparatus, which make preview display that reflects the print layout as faithfully as possible and is most easy
20 to see without requiring the user to designate any layout for preview display, upon making print preview display.

More specifically, it is another object of the present invention to provide a print control method and
25 apparatus, which display a preview image of a document including pages with various sizes and directions so

that a page with a maximum vertical size just fits in a preview display window, can efficiently use the display space, allow the user to preview the entire page by horizontally scrolling the display window, allow the user to visually understand relative page sizes in preview display by zooming other pages at the same ratio as the maximum page, and also allow the user to recognize not only the relative size but also the actual size by displaying the size of the designated page.

In order to achieve the above object, one aspect of the present invention has the following arrangement.

That is, a print control apparatus comprises:
search means for searching pages included in a print job for a page with a maximum size;
zoom means for zooming all pages included in the print job in a scale at which the page with the maximum size falls within a predetermined frame; and
display means for displaying preview images of all the zoomed pages.

Preferably, when a page is deleted from the stored print job, pages included in the print job are searched again for a page with a maximum size, and all pages included in the print job are displayed as preview images in a scale at which the page with the maximum size falls within the frame.

Preferably, the scale at which the page with the maximum size falls within the frame is a scale at which a vertical dimension of the page with the maximum size becomes smaller than a vertical dimension of the frame.

5 Preferably, when a page displayed within the frame is designated, a size of the designated page is displayed.

The apparatus preferably further comprises means for printing the stored print job.

10 The apparatus preferably further comprises storage means for storing print data in units of print jobs.

Other features and advantages of the present invention will be apparent from the following
15 description taken in conjunction with the accompanying drawings, in which like reference characters designate the same or similar parts throughout the figures thereof.

20 BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention and, together with the description, serve to explain the principles
25 of the invention.

Fig. 1 is a block diagram for explaining the arrangement of a print control apparatus according to an embodiment of the present invention;

Fig. 2 is a block diagram showing the arrangement
5 of a typical print system built by a host computer to which a printer is connected;

Fig. 3 is a block diagram showing the arrangement of a print system which temporarily spools intermediate codes before a print command from an application is
10 converted into a print control command;

Fig. 4 is a sectional view for explaining the printer in the present invention;

Fig. 5 is a flow chart showing the process in a spooler 302;

15 Fig. 6 is a flow chart showing print control in a spool file manager 304;

Fig. 7 is a flow chart showing the process in a despooler 305;

Fig. 8 shows an example of a print setup window;

20 Fig. 9 shows an example of a print spool setup window;

Fig. 10 shows an example of a data format to be passed when the spool file manager 304 issues a print request of a physical page to the despooler 305;

Fig. 11 shows an example of a data format to be passed when the spool file manager 304 issues a print request of a physical page to the despooler 305;

Fig. 12 shows an example of a data format to be passed when the spool file manager 304 issues a print request of a physical page to the despooler 305;

Fig. 13 shows an example of a data format to be passed when the spool file manager 304 issues a print request of a physical page to the despooler 305;

Fig. 14 shows an example of a data format to be passed when the spool file manager 304 issues a print request of a physical page to the despooler 305;

Fig. 15 is a flow chart showing a setup change process in a setup change editor 307;

Fig. 16 shows an example of a window that displays a list of print jobs spooled in the spool file manager 304;

Fig. 17 shows an example of a window of a previewer 306;

Fig. 18 shows an example of a window of the setup change editor 307;

Fig. 19 is a flow chart showing the process when data created by an application program or the like is printed with store designation;

Fig. 20 is a flow chart showing details of step S1903 in Fig. 19;

Fig. 21 is a flow chart showing the processing sequence upon operation of an edit button or combine button while a job is selected from a job list;

Fig. 22 is a flow chart showing the sequence for
5 displaying a preview window upon operation of an edit button or combine button while a job is selected from a job list;

Fig. 23 is a flow chart showing details of step S2203 in Fig. 22;

10 Fig. 24 is a flow chart showing details of step S2204 in Fig. 22;

Fig. 25 is a flow chart showing details of step S2205 in Fig. 22;

Fig. 26 shows a display example of a job list;

15 Fig. 27 is a flow chart showing the sequence for rendering a page template;

Fig. 28 shows an example of preview display of pages having different sizes or directions; and

Fig. 29 shows an example of preview display when
20 a page with a maximum size is deleted from the display shown in Fig. 28.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Preferred embodiments of the present invention
25 will be described hereinafter.

<Arrangement of Printer Control System>

Fig. 1 is a block diagram for explaining the arrangement of a printer control system according to an embodiment of the present invention. Note that the present invention can be applied to any of a standalone
5 device, a system built by a plurality of devices, and a system in which devices are connected via a network such as a LAN, WAN, or the like to execute processes, as long as the functions of the present invention are implemented.

10 Referring to Fig. 1, a host computer 3000 comprises a CPU 101 that processes a document including figures, images, text, tables (including a spreadsheet or the like), and the like on the basis of a document processing program stored in a program ROM in a ROM 3
15 or an external memory 111, and systematically controls devices connected to a system bus 104. The program ROM in the ROM 103 or external memory 111 stores an operating system program (to be referred to as an OS hereinafter) or the like as a control program of the
20 CPU 101, a font ROM in the ROM 103 or the external memory 111 stores font data or the like used in the document process, and a data ROM in the ROM 103 or the external memory 111 stores various data used upon executing the document process. A RAM 102 serves as a
25 main memory, work area, and the like of the CPU 101.

A keyboard controller (KBC) 105 controls key input from a keyboard 109 and a pointing device (not shown). A CRT controller (CRTC) 106 controls display of a CRT display (CRT) 110. Reference numeral 107
5 denotes a disk controller (DKC) which controls access to the external memory 111 such as a hard disk (HD), floppy disk (FD), and the like, which store a boot program, various application programs, font data, user files, edit files, a printer control command generation
10 program (to be referred to as a printer driver hereinafter), and the like. A printer controller (PRTC) 108 is connected to a printer 1500 via a two-way interface (interface) 121 to implement a communication control process with the printer 1500.

15 Note that the CPU 101 rasterizes outline font data on a display information RAM assured on, e.g., the RAM 102 to realize WYSIWYG on the CRT 110. The CPU 101 opens various registered windows on the basis of commands instructed by a mouse cursor (not shown) or
20 the like on the CRT 110, and executes various data processes. The user can set a print processing method for the printer driver including the printer setup and print mode selection by opening a window that pertains to the print setups upon executing a print process.

25 The printer 1500 is controlled by a CPU 112. The printer CPU 112 outputs an image signal as output

information to a print unit (printer engine) 117, which is connected to a system bus 115, on the basis of a control program or the like stored in a program ROM in a ROM 113, or a control program or the like stored in an external memory 114. The program ROM in the ROM 113 stores the control program and the like of the CPU 112. A font ROM in the ROM 113 stores font data or the like used upon generating the output information, and a data ROM in the ROM 113 stores information and the like used on the host computer when the printer has no external memory 114 such as a hard disk or the like.

The CPU 112 can communicate with the host computer via an input unit 118, and can inform the host computer 3000 of information or the like in the printer. A RAM 119 serves as a main memory, work area, and the like of the CPU 112, and its memory size can be expanded by an option RAM connected to an expansion port (not shown). Note that the RAM 119 is used as an output information rasterizing area, environment data storage area, NVRAM, and the like. Access to the aforementioned external memory 114 such as a hard disk (HD), IC card, or the like is controlled by a memory controller (DKC) 120. The external memory 114 is connected as an option, and stores font data, an emulation program, form data, and the like. Reference

numeral 1501 denotes a control panel on which operation switches, LED indicators, and the like are arranged.

The number of external memories 114 is not limited to one, but a plurality of external memories 114 may be connected. That is, a plurality of option font cards in addition to built-in fonts and external memories that store programs for interpreting printer control languages of different language systems may be connected. Furthermore, an NVRAM (not shown) may be connected, and may store printer mode setup information from the control panel 1501.

Fig. 2 shows the configuration of typical print processing software in the host computer to which a printing apparatus such as a printer or the like is connected directly or via a network. An application program (to be simply referred to as an application hereinafter) 201, graphic engine 202, printer driver 203, and system spooler 204 are program modules which are stored as files in the external memory 111, and are loaded onto the RAM 102 by the OS or a module that uses the corresponding module upon execution. The application 201 and printer driver 203 can be added to the files stored in the HD using the FD in the external memory 111 or a CD-ROM (not shown), or via a network (not shown). The application 201 stored in the external memory 111 is loaded onto the RAM 102 upon

execution. When the application 201 executes a print process with respect to the printer 1500, it outputs (renders) data using the graphic engine 202 which is similarly loaded onto the RAM 102 upon execution.

5 The graphic engine 202 loads a printer driver 203 which is prepared for each printing apparatus from the external memory 111 onto the RAM 102, and sets the output from the application 201 in the printer driver 203. The graphic engine 202 then converts a GDI
10 (Graphic Device Interface) function received from the application 201 into a DDI (Device Driver Interface) function, and outputs the DDI function to the printer driver 203. The printer driver 203 converts the DDI function received from the graphic engine 202 into a
15 control command, e.g., PDL (Page Description Language) that the printer can recognize. The converted printer control command is output as print data to the printer 1500 via the interface 121 by the system spooler 204 which is loaded onto the RAM 102 by the OS.

20 The print system of this embodiment also has an arrangement for temporarily spooling print data from the application as intermediate codes, as shown in Fig. 3, in addition to the print system constructed by the printer and host computer shown in Fig. 2.

25 <Print-related Software Modules in Embodiment>

Fig. 3 shows the expanded system of Fig. 2. This system temporarily generates a spool file 303 consisting of intermediate codes upon sending a print command from the graphic engine 202 to the printer driver 203. In the system shown in Fig. 2, the application 201 is released from the print process when the printer driver 203 has converted all print commands from the graphic engine 202 into printer control commands. By contrast, in the system shown in Fig. 3, a spooler 302 converts all print commands into intermediate code data, and the application 201 is released from the print process when it outputs print commands to the spool file 303. Normally, the latter system can shorten the processing time. In the system shown in Fig. 3, data as the contents of the spool file 303 can be processed. In this way, functions such as enlargement/reduction, reduced-scale print of a plurality of pages on one page, and the like that the application does not have can be implemented for print data from the application.

For these purposes, the system of this embodiment is attained by expanding the system shown in Fig. 2 to spool data as intermediate codes, as shown in Fig. 3. In order to process print data, setups are normally made from a window provided by the printer driver 203,

which saves the setup contents on the RAM 102 or external memory 111.

The arrangement in Fig. 3 will be explained in detail below. As shown in Fig. 3, in this expanded
5 processing system, a dispatcher 301 receives a DDI function as a print command from the graphic engine 202. When the print command (DDI function) that the dispatcher 301 receives from the graphic engine 202 is based on a print command (GDI function) issued from the
10 application 201 to the graphic engine 202, the dispatcher 301 loads the spooler 302 stored in the external memory 111 onto the RAM 102, and sends the print command (DDI function) to the spooler 302 in place of the printer driver 203.

15 The spooler 302 interprets the received print command, converts it into intermediate codes in units of pages, and outputs the codes to the spool file 303. The spool file of intermediate codes stored in units of pages is called a page description file (PDF). Since
20 one PDF corresponds to one print job, the spooled PDF is also often called a job or print job simply. The spooler 302 acquires processing setups (N-up, two-side, staple, color/monochrome designation, or the like) associated with print data set in the printer driver
25 203 from the printer driver 203, and saves them as a setup file for each job in the spool file 303. The

setup file stored in units of jobs is called a job
setup file (also called an SDF as an abbreviation for a
spool description file). The job setup file will be
described later. Note that the spool file 303 is
5 generated as a file on the external memory 111, but may
be generated on the RAM 102. Furthermore, the spooler
302 loads a spool file manager 304 stored in the
external memory 111 onto the RAM 102, and informs the
spool file manager 304 of the generation state of the
10 spool file 303. After that, the spool file manager 304
checks if a print process can be done in accordance
with the contents of the processing setups associated
with print data, which are saved in the spool file 303.

If the spool file manager 304 determines that the
15 print process can be done using the graphic engine 202,
it loads a despooler 305 stored in the external memory
111 onto the RAM 102, and instructs the despooler 305
to execute the print process of the page description
files of intermediate codes described in the spool file
20 303.

The despooler 305 processes the page description
files of intermediate codes included in the spool file
303 in accordance with the job setup file which is
included in the spool file 303 and includes processing
25 setup information, re-generates a GDI function, and
outputs it via the graphic engine 202 once again.

When the print command (DDI function) that the dispatcher 301 receives from the graphic engine 202 is based on a print command (GDI function) issued from the despooler 305 to the graphic engine 202, the dispatcher
5 301 sends the print command to the printer driver 203 in place of the spooler 302.

The printer driver 203 generates a printer control command described in a page description language or the like on the basis of the DDI function
10 acquired from the graphic engine 202, and outputs the generated command to the printer 1500 via the system spooler 204.

Furthermore, Fig. 3 shows an example which includes a previewer 306 and setup change editor 307 in
15 addition to the expanded system described so far, and allows a print preview process, print setup change process, and combination process of a plurality of jobs.

In order to implement the print preview process, print setup change process, and combination process of
20 a plurality of jobs, the user must designate "store" on a pull-down menu 901 as a means for "designating an output destination" in a property window of the printer driver shown in Fig. 9. When the user wants to only
25 preview, he or she can select "preview" as designation of the output destination.

The contents set on the property window of the printer driver in this way are stored in a structure (for example, a structure called DEVMODE in Windows OS available from Microsoft Corp.) provided by the OS as a
5 setup file. That structure includes, e.g., store designation. Store designation is a setup for storing a print command and processing setup in the spool file 303. When the spool file manager 304 reads the processing setup via the printer driver 203 and that
10 setup includes store designation, the spool file 303 generates and stores a page description file and job setup file, as described above. Then, the window of the spool file manager 304 pops up, as shown in Fig. 16, and displays a list of jobs spooled by the spool file
15 303. Fig. 16 shows an example wherein four jobs are spooled, and operations for each job can be selected from a menu bar or by pressing menu icons below the menu bar. Operations that can be selected from the menu bar are the same as those of the menu icons. The
20 following types of operations are available. Note that each operation is done while selecting a desired job. That is, there are 12 operations:

(1) "print": executes a given job while selecting that job. That is, this operation prints the
25 designated spool file.

(2) "save & print": executes a print process while saving a job of the selected intermediate codes.

(3) "preview": displays output preview in consideration of the print setups.

5 (4) "delete": deletes the selected job.

(5) "copy": generates a copy of the selected job.

(6) "combine": combines a plurality of jobs into one job.

10 (7) "divide": divides the combined job into a plurality of original jobs.

(8) "job edit" changes the print setups (layout setup, finishing setup, and the like) of an independent or combined job.

15 (9) "move to top": moves the print order of a given job to the top of a job list.

(10) "move up by one": advances the print order of a given job by one.

(11) "move down by one": delays the print order of a given job by one.

20 (12) "move to last": moves the print order of a given job to the last of a job list.

When "preview" of an independent or combined job is designated on the window (Fig. 16) of the spool file manager, the previewer 306 stored in the external
25 memory 111 is loaded onto the RAM 102, and is

instructed to execute a preview process of a job of the intermediate codes described in the spool file 303.
(Previewer)

The previewer 306 sequentially reads out page
5 description files (PDF) of intermediate codes included in the spool file 303, processes them in accordance with the contents of processing setup information included in the job setup file (SDF) stored in the spool file 303, and outputs a GDI function to the
10 graphic engine 202. The graphic engine 202 can output a preview window onto the screen by outputting rendering data on its own client area.

The graphic engine 202 can appropriately render in correspondence with the designated output
15 destination. The previewer 306 implements preview by the method of processing intermediate codes included in the spool file 303 in accordance with the contents of the processing setups included in the spool file 303 and outputting them using the graphic engine as in the
20 despooler 305. In this way, since the processing setups set in the printer driver are stored as a job setup file in the spool file 303 and data of the page description file are processed and output based on the job setup file, a print preview approximate to an
25 actual printout can be provided to the user in correspondence with the way actual rendering data is

printed, and designated processes (e.g., an N-up
process (for laying out and printing N logical pages on
one physical page), a two-sided print process, a
bookbinding print process, a stamp process, and the
5 like). Since the preview function of conventional
application software such as document creation software
renders based on page setups in that application, the
print setups in the printer driver are not reflected in
preview, and the user cannot recognize a preview of an
10 image to be actually printed out.

One logical page is one page in data created by
the application, and one physical page corresponds to
one surface of one sheet (e.g., one paper sheet). More
specifically, when the N-up process is designated,
15 images for N pages created by the application are laid
out and printed on a single sheet in a reduced scale.

By executing the preview process in this fashion,
a large preview image of an image processed in
accordance with the print processing setups saved in
20 the spool file 303 is displayed on the screen by the
previewer 306, as shown in Fig. 17. After that, the
previewer 306 is closed in response to the user's
non-display instruction (designation of "close)), and
the control shifts to the window (Fig. 16) of the spool
25 file manager.

When the user wants to print the contents displayed by the previewer 306, he or she issues a print request by selecting "print" or "save & print" on the spool file manager 304. In response to the print
5 request, the despooler 305 generates a GDI function by processing each page description file based on the job setup file, and passes it to the graphic engine 202. Then, a print command is sent to the printer driver 203 via the dispatcher 301, thus executing the print
10 process.

(Setup Change Editor)

A setup change process using the setup change editor 307 will be explained below.

The setup change process can be done for a
15 "store"-designated job in Fig. 9 as in the preview process. The window of the spool file manager 304 pops up in the same sequence as in the preview process, and displays a list of spooled jobs. A setup change instruction is issued by designating "job edit" for the
20 selected spool file on the window (Fig. 16) of the spool file manager. When the setup change instruction is issued, the setup change editor 307 stored in the external memory 111 is loaded onto the RAM and is instructed to display current or default processing
25 setups. Then, a job setup window shown in Fig. 18 is displayed.

The setup change editor 307 acquires the job setup file of the "job edit"-designated job, and default values of the job setup window in Fig. 18 are changed on the basis of setup items designated in that job setup file. In the example shown in Fig. 18, the job setup file of the "job edit"-designated file is designated with the number of copies: 1, print method: one-sided, staple: none, layout: 1 page/sheet, and the like.

10 This setup change editor 307 can also make a small preview output on the window shown in Fig. 18 by processing each page description file of intermediate codes stored in the spool file 303 in accordance with the contents of the processing setups included in the job setup file stored in the spool file 303, and outputting them onto its own client area using the graphic engine.

Also, this editor can change and correct the contents of the processing setups included in the job setup file stored in the spool file 303. In this case, the user interface on the setup change editor 307 may have items that the printer driver 203 can set, or the user interface of the printer driver 203 itself may be called. As shown in Fig. 18, the number of copies, the print method (one-side, two-side, bookbinding print), staple (saddle finisher, or the like), page layout,

layout order, and the like can be designated. Upon pressing "detailed setups", most of items that the printer driver can designate can be re-set. However, changes of setups that pertain to print quality such as the resolution, graphic mode, and the like are not permitted.

When the changed items are confirmed in accordance with a confirmation request on the setup change editor 307, the control shifts to the spool file manager 304. The confirmed print setups that have been changed are saved. In this case, the setups are not saved in an original job setup file, but a new job output setup file used in the job edit process or the like is created to save the setups. Details of the job output setup file will be described later using Fig. 10 and the subsequent figures.

If the user wants to print in accordance with the changed setup contents as in the previewer 306, the spool file manager 304 issues a print request. The print request is sent to the graphic engine 202, and a print command is sent to the printer driver 203 via the dispatcher 301, thus executing the print process.

On the window (Fig. 16) of the spool file manager, the user can designate to combine a plurality of print jobs to execute them as a single print job. This process is also premised on the "store"-designated job

on the property window of the printer driver shown in Fig. 9 as in the preview and setup change processes.

When the user wants to combine print jobs, he or she calls the printer driver 203 from the application 5 201, and selects "store" from the user interface shown in Fig. 9. With this selection, the print job is stored in the spool file 303, and the window (Fig. 16) of the spool file manager pops up, as shown in Fig. 16. The spooled job is displayed as a list on the window of 10 the spool file manager. By repeating the same operation from the application 201, a plurality of jobs are spooled, and a list of jobs is displayed on the window of the spool file manager 304.

When the user selects a plurality of jobs from 15 the list and designates "combine", the setup change editor 307 stored in the external memory 111 is loaded onto the RAM 102 and is instructed to display the processing setups of the first job on the list or default setups. Then, a combine setup window shown in 20 Fig. 18 is displayed. In this embodiment, the same window as the setup change window is used as the combine setup window, but another window may be used.

The setup change editor 307 processes each page 25 description file of intermediate codes included in the spool file 303 in accordance with the contents of the processing setups included in job setup information

stored in the spool file 303, and outputs the processed data for all jobs designated as the combined job to its own client area using the graphic engine 202, thus outputting these jobs on the screen. In this case,
5 small preview images of all the selected jobs can be displayed on the preview region shown in Fig. 18. Upon generating the combined job, a job output setup file that expands the job setup files of the individual jobs is generated. This job output setup file is also
10 generated in the job edit process. That is, one job output setup file is generated for each job and also for the combined job.

In this case, images of the individual jobs may be displayed using the processing setups before they
15 are combined, or may be displayed by changing and correcting their setups to common processing setups of the combined job. In this case, the user interface on the setup change editor 307 may have items that the printer driver 203 can set, or the user interface of
20 the printer driver 203 itself may be called.

When the combined job and changed items are confirmed in accordance with a confirmation request on the setup change editor 307, as described above, the control shifts to the spool file manager 304. With
25 these operations, the plurality of jobs selected

previously are displayed as a single combined job on the window of the spool file manager.

When the user wants to print in accordance with the changed setup contents as in the previewer 306, the spool file manager 304 issues a print request. The print request is sent to the graphic engine 202, and a print command is sent to the printer driver 203 via the dispatcher 301, thus executing the print process.

<Arrangement of Laser Beam Printer>

Fig. 4 is a sectional view of a color laser printer having a two-sided print function as an example of the printer 1500.

This printer forms an electrostatic latent image by scanning the surface of a photosensitive drum 15 with a laser beam modulated by image data of each color obtained based on print data input from the host computer 3000 by a polygonal mirror 31. The electrostatic latent image is developed by toner to obtain a visible image, and visible images of all colors are transferred in turn onto an intermediate transfer drum 9 to form a color visible image. The color visible image is transferred onto a transfer medium 2, thus fixing the color visible image on the transfer medium 2. An image forming unit that makes the aforementioned control comprises a drum unit 13 having the photosensitive drum 15, a primary charger

having a contact charging roller 17, a cleaning unit, a
developing unit, the intermediate transfer drum 9, a
paper feed unit including a paper cassette 1 and
various rollers 3 and 4, a transfer unit including a
5 transfer roller 10, and a fixing unit 25.

The drum unit 13 integrates the photosensitive
drum (photosensitive body) 15 and a cleaner container
14 which has a cleaning mechanism that also serves as a
holder of the photosensitive drum 15. The drum unit 13
10 is detachably supported on a printer main body, and is
easily exchanged as a unit in correspondence with the
service life of the photosensitive drum 15. The
photosensitive drum 15 is prepared by applying an
organic photoconductor layer on the outer surface of an
15 aluminum cylinder, and is rotatably supported by the
cleaner container 14. The photosensitive drum 15
rotates upon receiving the driving force of a driving
motor (not shown), and the driving motor rotates the
photosensitive drum 15 counterclockwise in accordance
20 with image forming operation. An electrostatic latent
image is formed by selectively exposing the surface of
the photosensitive drum 15. In a scanner unit 30, a
modulated laser beam is reflected by the polygonal
mirror which rotates by a motor 31a in synchronism with
25 the horizontal sync signal of an image signal, and

strikes the photosensitive drum via a lens 32 and reflection mirror 33.

The developing unit comprises three color developers 20Y, 20M, and 20C for developing yellow (Y), magenta (M), and cyan (C) images, and a single black developer 21B for developing a black (B) image. The color developers 20Y, 20M, and 20C and the black developer 21B respectively have sleeves 20YS, 20MS, 20CS, and 21BS, and coating blades 20YB, 20MB, 20CB, and 21BB which are in press contact with the outer surfaces of these sleeves 20YS, 20MS, 20CS, and 21BS. Also, the three color developers 20Y, 20M, and 20C respectively have coating rollers 20YR, 20MR, and 20CR.

The black developer 21B is detachably attached to the printer main body, and the color developers 20Y, 20M, and 20C are detachably attached to a developing rotary 23 which rotates about a rotation shaft 22.

The sleeve 21BS of the black developer 21B is set to have a gap as small as, e.g., 300 μm with respect to the photosensitive drum 15. In the black developer 21B, toner is fed by a feed member built in the developer, and is applied by the coating blade 21BB to the outer surface of the sleeve 21BS which rotates clockwise, thus charging the toner by triboelectrification. By applying a developing bias to the sleeve 21BS, the photosensitive drum 15 undergoes development in

accordance with an electrostatic latent image, thus forming a visible image on the photosensitive drum 15 by black toner.

The three color developers 20Y, 20M, and 20C rotate upon rotation of the developing rotary 23 in image formation, and a predetermined one of the sleeves 20YS, 20MS, and 20CS faces the photosensitive drum 15 to have a gap as small as 300 μ m. In this manner, a predetermined one of the color developers 20Y, 20M, and 20C stops at the developing position where it faces the photosensitive drum 15, thus forming a visible image on the photosensitive drum 15.

Upon forming a color image, the developing rotary 23 rotates once per rotation of the intermediate transfer drum 9 to execute developing processes in the order of the yellow developer 20Y, magenta developer 20M, cyan developer 20C, and black developer 21B. After four rotations of the intermediate transfer drum 9, visible images are formed in turn by yellow, magenta, cyan, and black toners, thus forming a full-color visible image on the intermediate transfer drum 9.

The intermediate transfer drum 9 contacts the photosensitive drum 15 and rotates upon rotation of the photosensitive drum 15. The drum 9 rotates clockwise upon forming a color image, and four visible images are transferred in turn onto the drum 9 from the

photosensitive drum 15. The transfer roller 10 (to be described later) contacts the intermediate transfer drum 9 upon forming an image, and clamps and conveys a transfer medium 2, thus simultaneously transferring a color visible image on the intermediate transfer roller 9 onto the transfer medium 2. A TOP sensor 9a and RS sensor 9b for detecting the position of the intermediate transfer drum 9 in its rotational direction, and a density sensor 9c for detecting the density of the toner image transferred onto the intermediate transfer drum are arranged around the intermediate transfer drum.

The transfer roller 10 comprises a transfer charger which is supported to be movable toward or away from the photosensitive drum 15, and is prepared by winding a middle-resistance foamed elastic member around a metal shaft.

The transfer roller 10 is located at its lower position, as indicated by the solid line in Fig. 4, so as not to disturb color visible images, while color visible images are transferred in turn onto the intermediate transfer drum 9. After the four color visible images are formed on the intermediate transfer drum 9, the transfer roller 10 moves to its upper position indicated by the dotted line in Fig. 1 by a cam member (not shown) in synchronism with the transfer

timing of the formed full-color visible image onto the transfer medium 2. In this manner, the transfer roller 10 is brought into press contact with the intermediate transfer drum 9 at a predetermined pressure via the transfer medium 2, and is applied with a bias voltage, thus transferring the full-color visible image on the intermediate transfer drum 9 onto the transfer medium 2.

The fixing unit 25 fixes the transferred full-color visible image while conveying the transfer medium 2, and comprises a fixing roller 26 for heating the transfer medium 2, and a pressing roller 27 for pressing the transfer medium 2 against the fixing roller 26. The fixing roller 26 and pressing roller 27 are formed into a hollow shape, and heaters 28 and 29 are respectively built therein. That is, the transfer medium 2 that holds the full-color visible image is conveyed by the fixing roller 26 and pressing roller 27, and the toner image is fixed on its surface by applied heat and pressure.

After the visible image is fixed, the transfer medium 2 is exhausted onto an exhaust unit 37 via exhaust rollers 34, 35, and 36, thus ending the image forming operation.

The cleaning means cleans any residual toner on the photosensitive drum 15 and intermediate transfer drum 9, and waste toner after the toner image formed on

the photosensitive drum 15 is transferred onto the intermediate transfer drum 9 or waste toner after the four color visible images formed on the intermediate transfer drum 9 are transferred onto the transfer medium 2 is stored in the cleaner container 14.

The transfer medium (recording sheet) 2 which is to undergo a print process is picked up from the paper tray or cassette 1 by the roller 3, and is conveyed while being clamped between the intermediate transfer roller 9 and transfer roller 10 to record a color toner image thereon. The toner image is fixed when the transfer medium 2 passes through the fixing unit 25. A guide 38 forms a convey path to guide the recording sheet toward the upper exhaust unit in a one-sided print process, but forms a path to guide it to a lower two-side unit in a two-sided print process.

The recording sheet guided to the two-side unit is temporarily fed to a portion (a convey path indicated by the two-dashed chain line) below the tray 1 by convey rollers 40, is then conveyed in the reverse direction, and is fed to a two-side tray 39. On the two-side tray 39, the paper sheet is upside down to that placed on the paper tray 1, and its convey direction is reversed. In this state, a toner image is transferred and fixed again, thus achieving the two-sided print process.

<Saving Process of Print Intermediate Data>

Fig. 5 is a flow chart showing the processing in the step of saving in units of pages upon generating the spool file 303 in the spooler 302.

5 In step 501, the spooler 302 receives a print request from the application via the graphic engine 202. The application displays a dialog that prompts the user to input print setups, as shown in Fig. 8, and the print setups input on this dialog are passed from the
10 printer driver to the spooler 303. The setup input dialog shown in Fig. 8 includes a setup item 801 that determines the number of logical pages to be laid out per physical page, and the like.

 In step 502, the spooler 302 checks if the
15 received print request is a job start request. If it is determined in step 502 that the received print request is a job start request, the flow advances to step 503, and the spooler 302 generates a spool file 303 for temporarily saving intermediate data.
20 Subsequently, the spooler 302 informs the spool file manager 304 of the progress of the print process in step 504, and resets its page counter to 1 in step 505. The spool file manager 304 reads and stores information, processing setups, and the like of a job, the print
25 process of which has started, from the spool file 303.

On the other hand, if it is determined in step 502 that the received print request is not a job start request, the flow advances to step 506.

The spooler checks in step 506 if the received
5 request is a job end request. If it is determined that the received request is not a job end request, the flow advances to step 507 to check if the received request is a new page request. If it is determined in step 507 that the received request is a new page request, the
10 flow advances to step 508 to inform the spool file manager 304 of the progress of the print process. The spooler 302 then increments the page counter, closes a page description file that stores intermediate codes, and generates the next page description file.

15 If it is determined in step 507 that the received print request is not a new page request, the flow advances to step 509, and the spooler 302 prepares for export of intermediate codes to a page description file.

In step 510, the spooler 302 converts a DDI
20 function of the print request into intermediate codes to store the print request in the spool file 303. In step 511, the spooler 302 writes the print request (intermediate codes) that has been converted into a storable format in a page description file of the spool
25 file 303 in step 510. After that, the flow returns to step 501 to receive a print request from the

application again. The spooler 302 repeats a series of processes from steps 501 to 511 until it receives a job end request (EndDoc). The spooler 302 simultaneously acquires information such as processing setups and the like stored in the DEVMODE structure from the printer driver, and stores such information in the spool file 303 as a job setup file. On the other hand, if it is determined in step 506 that the print request from the application is a job end request, since the spooler 302 has received all print requests from the application, the flow advances to step 512 to inform the spool file manager 304 of the progress of the print process, thus ending the processing.

<Generation of Spool File>

Fig. 6 is a flow chart showing details of control between the spool file 303 generation process and a print data generation process (to be described later) in the spool file manager 304.

In step 601, the spool file manager 304 receives a print process progress message from the spooler 302 or despooler 305.

The spool file manager 304 checks in step 602 if the progress message is a print start message which is sent from the spooler 302 in step 504 described above. If YES in step 602, the flow advances to step 603, and

the spool file manager 304 reads the print processing setups from the spool file 303 to start job management.

On the other hand, if it is determined in step 602 that the received progress message is not a print start message from the spooler 302, the flow advances to step 604, and the spool file manager 304 checks if the progress message is a print end message of one logical page which is sent from the spooler 302 in step 508 mentioned above. If the progress message is a print end message of one logical page, the flow advances to step 605 to store logical page information for that logical page.

It is then checked in step 606 if a print process of n logical pages that have been spooled at that time onto one physical page can start. If YES in step 606, the flow advances to step 607 to determine a physical page number on the basis of the number of logical pages assigned to one physical page to be printed.

As for a computation of a physical page, for example, when the processing setups lay out four logical pages on one physical page, the first physical page becomes ready for print when the fourth logical page has been spooled, thus determining the first physical page. Subsequently, the second physical page becomes ready for print when the eighth logical page has been spooled.

Also, even when the total number of logical pages is not a multiple of the number of logical pages to be laid out per physical page, logical pages to be laid out per physical page can be determined by a spool end message in step 512.

In step 608, the spool file manager 304 saves information such as the logical page numbers which form the physical page that is ready for print, the physical page number of that physical page, and the like in a job output setup file (a file including physical page information) in the format shown in Fig. 10, and informs the despooler 305 that physical page information for one physical page has been added. After that, the flow returns to step 601 to wait for the next message. In this embodiment, when print data for one page, i.e., logical pages that form one physical page have been spooled, a print process can start even when print jobs to be spooled still remain.

On the other hand, if it is determined in step 604 that the progress message is not a print end message of one logical page, the flow advances to step 609, and the spool file manager 304 checks if the progress message is a job end message sent from the spooler 302 in step 512 mentioned above. If YES in step 609, the flow advances to step 606 described above.

On the other hand, if the progress message is not a job end message, the flow advances to step 610, and the spool file manager 304 checks if the received message is a print end message of one physical page
5 from the despooler 305. If the received message is a print end message of one physical page, the flow advances to step 611 to check if print processes for the processing setups are complete. If YES in step 611, the flow advances to step 612 to send a print end
10 message to the despooler 305.

On the other hand, if it is determined that print processes for the processing setups are not complete yet, the flow advances to step 606 described above. The despooler 305 in this embodiment assumes one
15 physical page as a unit for the print process. In step 608, information required for executing the print process of one physical page is saved in a file, so that such information can be used again. However, if such information need not be used again, a high-speed
20 medium such as a shared memory or the like may be used to overwrite information in turn in units of physical pages, thus achieving both high processing speed and resource savings. On the other hand, when the progress of spooling is faster than that of despooling, or when
25 despooling starts after completion of spooling of all pages, a message indicating that a plurality of

physical pages or all physical pages are ready for
print is sent in accordance with the progress on the
despooling side in place of sending a page print ready
message for each physical page in step 608, thus

5 reducing the number of messages.

If it is determined in step 610 that the message
is not a print end message of one physical page from
the despooler, the flow advances to step 613, and the
spool file manager 304 checks if the message is a print
10 end message from the despooler 305. If it is
determined that the message is a print end message from
the despooler 305, the flow advances to step 614, and
the spool file manager 304 deletes the corresponding
page description files in the spool file 303, thus
15 ending the processing. On the other hand, if the
message is not a print end message from the despooler
305, the flow advances to step 615 to execute another
normal process and to then wait for the next message.

<Output of Spool File>

20 Fig. 7 is a flow chart showing details of the
print data generation process in the despooler 305.

The despooler 305 reads out required information
(page description file and job setup file) from the
spool file 303 in response to the print request from
25 the spool file manager 304, and generates print data.
The method of transferring the generated print data to

the printer has already been explained with reference to Fig. 3.

Upon generating print data, the despooler 305 receives a message from the spool file manager 304 in
5 step 701. The despooler 305 checks in step 702 if the input message is a job end message. If YES in step 702, the flow advances to step 703 to set an end flag, and the flow then jumps to step 705.

On the other hand, if it is determined in step
10 702 that the received message is not a job end message, the flow advances to step 704 to check if the print start request of one physical page in step 608 mentioned above is received. If it is determined in step 704 that the received message is not a start
15 request, the flow advances to step 710 to execute an error process, and the flow returns to step 701 to wait for the next message. On the other hand, if it is determined in step 704 that the received message is a print start request of one physical page, the flow
20 advances to step 705, and the despooler 305 saves the IDs of physical pages, the print ready message of which was received in step 704.

The despooler 305 checks in step 706 if print
25 processes of all pages of the physical page IDs saved in step 705 are complete. If YES in step 706, the flow advances to step 707 to check if the end flag was set

in step 703 mentioned above. If YES in step 707, the despooler 305 determines that the job print process is complete, and sends its processing end message to the spool file manager 304, thus ending the processing.

5 If it is determined in step 707 that the end flag is not set, the flow returns to step 701 to wait for the next message. If it is determined in step 706 that physical pages which are ready for print still remain, the flow advances to step 708. In step 708, the
10 despooler 305 reads out unprocessed physical page IDs in turn from the saved physical page IDs, reads information required for generating print data of a physical page corresponding to each readout physical page ID, and executes a print process. The print
15 process is done by converting by the despooler 305 a print request command stored in the spool file 303 into a format (GDI function) that the graphic engine 202 can recognize, and transferring it to the printer driver.

 As for the processing setups that lay out a
20 plurality of logical pages on one physical page (to be referred to as an N-page print process hereinafter) as in this embodiment, conversion in this step is done in consideration of the layout upon reduction in scale. Upon completion of the required print process, the
25 despooler 305 sends a print data generation end message of one physical page to the spool file manager 304 in

step 709. The flow returns to step 706 to repeat the aforementioned processes until print processes for all the physical page IDs of print ready pages, which were saved in step 705, are complete.

5 The flow of the print process using the dispatcher 301, spooler 302, spool file manager 304, and despooler 305 has been explained. With the above process, since the application 201 is released from the print process at the timing at which the spooler 302
10 generates intermediate codes and stores them in the spool file 303, the application 201 can be released earlier than a case wherein a print command is directly output to the printer driver 203. Since intermediate files (page description file, job setup file) that
15 consider the print setups of the printer driver are temporarily saved in the spool file 303, the user can recognize a print preview of an image to be actually printed, and can combine or sort print jobs generated by a plurality of applications. Also, the user can
20 change print setups to execute a print process without launching the application again.

 In the print process using the spooler 302, a job output setup file is generated when the despooler 305 issues a print request to the graphic engine, and is
25 also generated when the preview process, job combine process, or the like is done. The job output setup

file is equivalent to a job setup file in case of an independent job, and is generated based on a plurality of pieces of job setup information in case of a combined job. The job output setup file will be explained below.

<Configuration of Job Output Setup File>

Fig. 10 shows an example of the job output setup file that saves information which is generated by the spool file manager 304 in step 608, and forms a print ready physical page. A field 1001 holds an ID that identifies a job, and may be held in the form of the name of a file or shared memory which saves this information. A field 1002 stores job setup information. The job setup information includes information unique to each job, such as a structure required for starting a job print process with respect to the graphic engine 202, designation of an N-page print process, designation of additional rendering of a page frame or the like, the number of copies, finishing designation such as staple, and the like. The job setup information in the field 1002 saves a required number of information in correspondence with the functions for a job. A field 1003 stores the number of physical pages of a job, and indicates the number of pieces of physical page information in correspondence with the value stored therein. Since this embodiment informs

the number of physical pages which are ready for print,
this field may be omitted. Fields 1004 to 1007 store
physical page information in correspondence with the
value stored in the field 1003. The physical page
5 information will be explained later using Fig. 12.

Fig. 11 shows an example of the job setup
information in the field 1002 shown in Fig. 10. A
field 1101 stores the total number of physical pages.
A field 1102 stores the total number of logical pages.
10 The fields 1101 and 1102 are used when the number of
pages is printed as additional information in addition
to print data. While a print process continues, these
fields store tentative values, or the spool file
manager 304 postpones generation of information of
15 print ready physical pages until the print process ends.
A field 1103 stores information indicating the number
of copies to be printed of the print job of interest.
A field 1104 stores information that designates if a
print process is done in units of copy sets, when
20 information set in the field 1103 indicates a print
process of a plurality of sets of copies. A field 1105
stores finishing information such as staple, punch,
Z-fold, and the like, which information is designated
when a finisher is available on the printer main body
25 or an external device. A field 1106 stores additional
print information, which saves information to be added

to a job such as decoration including a page frame or the like, additional information including a date or the like, the user name, the number of pages, watermark print, and the like. The number of fields included in this job setup information increases with increasing number of functions. For example, when a two-sided print function is available, a field for saving designation of two-sided print is added.

Fig. 12 shows an example of the physical page information in the field 1004 shown in Fig. 10. A first field 1201 stores a physical page number, which is a value used when the print order is managed or a physical page number is additionally printed. A field 1202 stores physical page setup information, which saves layout or color/monochrome setups when a layout or color/monochrome mode can be designated in units of physical pages. A field 1203 stores the number of logical pages assigned to the physical page of interest, and saves a value "4" or an ID indicating 4-page print when four pages are assigned per physical page.

A field 1204 and the subsequent fields save information of logical pages in correspondence with the number designated in the field 1203. Depending on the number of pages printed from the application 201, the actual number of page data sometimes becomes smaller than the number of pages designated by the field 1203.

In such case, logical page information saves special data indicating a blank page.

Fig. 13 shows an example of the physical page setup information in the field 1202. A field 1301 stores the layout order of logical pages on a physical page, and saves designation of the order that logical pages are laid out on a physical page (from upper left to right, from upper left to lower, and the like) in an N-page print process. In some systems, the field 1204 and the subsequent fields that store logical page information may be arranged not in a page number order but in the layout order in place of the setups in the field 1301.

A field 1302 stores information indicating the obverse or reverse surface of the two-sided print, which is used when, e.g., binding margins are to be formed on identical sides on the obverse and reverse surfaces. A field 1303 stores designation of a color or monochrome page, which is a value used when a printer has both monochrome and color modes, and color and monochrome pages of a document that includes both color and monochrome pages are to be printed in the color and monochrome modes, respectively. With this information, the color printer can change processes in units of pages as an auto color mode. That is, transfer control is done for a color page by completing

rotations of an intermediate transfer member
(intermediate transfer drum or belt) or transfer member
(transfer drum or belt) in correspondence with the
number of device colors (four rotations in case of
5 YMCK), and for a monochrome page by completing one
rotation for black.

A field 1304 stores additional print information,
which is used when additional information such as the
number of pages, date, or the like is printed on a
10 physical page. In the physical setup information, the
number of fields increases in correspondence with the
number of functions of the system.

Fig. 14 shows an example of logical page
information stored in the field 1204. A field 1401
15 stores the ID of a physical page. Using this ID, an
intermediate code of a page description file
corresponding to the logical page of interest is looked
up from the spool file 303. This field may store a
file or memory pointer, or an intermediate code itself
20 that forms a logical page, as long as the intermediate
code of a logical page can be accessed using this ID.

A field 1402 stores a logical page number, which
is used when the logical page number is printed as
additional information or as auxiliary information of
25 the logical page ID. Format information in a field
1403 saves various setup items that can be designated

in units of logical pages. For example, the format information saves additional print information such as a page frame and various kinds of setup information designated in units of logical pages such as an

5 enlargement/reduction ratio and the like. Also, the format information can save attribute information of a logical page such as color/monochrome information in units of logical pages if necessary. Conversely, if a system need not switch setups in units of local pages
10 or does not require any attribute information in units of logical pages, the field 1403 can be omitted.

The job output setup file has the aforementioned configuration. Note that the job setup file has nearly the same configuration. The job setup file saves a
15 print method (one-sided, two-sided, bookbinding print), a print layout (N-up, poster print), additional information (addition of watermark, date, user name), the number of copies, and paper size information for each job. Also, the job setup file saves the layout
20 order of logical pages, information indicating the obverse or reverse surface of two-sided print, color mode information, and the like in units of physical pages.

Furthermore, Fig. 3 shows the example in which
25 the setup change editor 307 having a function of changing the setups of a job is added to the expanded

system described so far. In this embodiment, the setup contents of an independent job are contained in a job setup file, and those of a combined job are contained in a job output setup file shown in Fig. 10. In

5 addition, these files are independent from the page description file that saves intermediate codes. Hence, the setups of each job can be changed by editing the job output setup file. The setup change editor 307 edits or partially rewrites the job output setup file
10 solely or in collaboration with the spool file manager 304, thus implementing the job setup change function.
<Processing Sequence of Setup Change>

Fig. 15 is a flow chart showing details of the job setup change process in the setup change editor 307.

15 In step 1501, the setup change editor reads a job setup file or job output setup file. The job output setup file is the same file as that read by the previewer 306 and despooler 305.

The flow advances to step 1502 to display the
20 read result to the user. In step S1503, the setup change editor interactively changes the setup contents by the aforementioned menu designation and the like with the user on the user interface shown in Fig. 18. This step may be attained in a batch manner that
25 changes contents in accordance with setup change

contents written in a file or the like in place of the interactive manner.

The flow advances to step 1504, and the setup change editor compares the initially read contents and
5 the currently designated setup contents to check if the contents have been changed. If the setup contents have been changed, the flow advances to step 1505 to generate a new job output setup file and inform the
10 pool manager file of the changes, thus ending the processing. If it is determined in step 1504 that the setup changes are not changed, the setup change editor informs the spool file manager of that fact, thus ending the processing.

A new job output setup file is generated in this
15 way. When an "OK" button 1801 is selected on the user interface window in Fig. 18, the new job output setup file is enabled, and the old job output setup file is deleted. When the job setup file of an independent job has been changed in place of the job output setup file,
20 the old file is saved without being deleted. When a "restore defaults" button 1802 is selected on the window shown in Fig. 18, the new job output setup file is deleted, and the old job output setup file is enabled and reflected in display.

25 This embodiment has explained the setup change editor 307 as an independent module. Alternatively,

the setup change editor 307 may be a part of the user interface of the spool file manager 304. Also, the setup change editor 307 may be implemented as follows. That is, the editor 307 does not actually write change
5 contents in the job output setup file and informs the spool file manager 304 of only the setup change contents, and the spool file manager 304 actually changes the job output setup file.

Fig. 3 shows the expanded system that combines a
10 plurality of print jobs and prints them as a single print job. An expansion for despooling and previewing a combined job will be explained below.

Normally, spool files 303 with the intermediate format are generated in units of jobs. In case of an
15 independent job, since a print process, setup change process, or the like is executed by sequentially reading out intermediate codes of respective logical pages in the job file to be processed, the logical page ID in the field 1401 can be implemented by a relative
20 or absolute offset which indicates the location of each logical page in a file. In case of a combined job, a spool file and page information which belongs to that job must be specified from the job ID in the field 1401. In this embodiment, a spool file is specified by
25 appending an ID that identifies a spool file to the logical page ID. In this case, only the field 1401 can

be modified. If the spool file can be identified, read of page information can be processed by the same logic as in the process of an independent job. In another implementation, when spool files are saved as

5 independent files in units of logical pages, the file name of each logical page may be used as the logical page ID in the field 1401.

<Preview Display in Store Process>

The sequence for displaying a print preview image
10 on the basis of a print job saved as intermediate data and a job output setup file will be explained below. When the user designates a store process of a print job from a menu 901, as shown in Fig. 9, in the print process from the application program, a print job
15 defined by intermediate codes and a job output setup file can be generated in the sequence shown in Fig. 5. As a result, a list of currently stored print jobs is displayed, as shown in Fig. 16. The user designates a desired print job from the print job list, and can edit
20 the print job, combine jobs, add the print job to the already combined print job, change the order of print jobs in the combined job, and so forth.

In this case, when the user designates a given print job from the list and designates an operation
25 such as edit, combine, or the like from the button or menu, a print preview window of the entire designated

job is displayed, as shown in Fig. 18. Note that this print preview window can also display a preview image of the page relationship in the entire independent or combined print job unlike a normal preview window
5 prepared by an application, which displays a preview image for each page.

Fig. 19 shows the sequence when data created by an application program or the like undergoes a print process while designating a store process. When the
10 user selects "store" from the menu 901 as the output destination on the window shown in Fig. 9, and starts the print process, the sequence shown in Fig. 9 is executed.

In step S1901, the spooler is launched to
15 generate and store intermediate data and a job output setup file. When "store" is designated, the spooler does not issue any print start instruction to the spool manager, and the intermediate data are held without being printed. The print job in this state is called a
20 stored print job in this embodiment.

The print job that has been converted into and held as intermediate data in step S1901 is added to the already stored print job list in step S1902. In this embodiment, the stored print job is held only during
25 execution of a program (the previewer 306 and setup change editor 307 in Fig. 3) for managing stored print

jobs, and is deleted upon quitting such program.

However, the stored print job may be held until it is actually deleted.

When a new print job is added to the stored print
5 job list, a list of these jobs is displayed in step
S1903, as shown in Fig. 16. Note that a print job held
as intermediate data is called a held job, and a job
selected for the combine or edit process is called a
target job.

10 <Display of Job List>

Fig. 20 is a flow chart showing details of step
S1903 in Fig. 19. Note that the sequence in Fig. 20 is
executed every time the state to be displayed has been
changed, e.g., when a job is selected from the job list,
15 thus updating the displayed job list.

It is checked in step S2001 if a plurality of
jobs are selected. If NO in step S2001, it is checked
in step S2002 if a job is selected. If YES in step
S2002, that job is determined as a job of interest, and
20 an edit button is enabled. The edit button is a button
1608 in Fig. 16. Fig. 16 shows a state immediately
after a single job is selected, and the edit button is
enabled.

On the other hand, if no job is selected, a job
25 which was selected in the previous process is
determined as a job of interest in step S2004. If no

such job is available, i.e., if the job list is displayed for the first time, the first job in the job list is determined as a job of interest.

After the job of interest is determined, a job
5 which cannot be combined with the job of interest is picked up from the held jobs, and the effect and reason why the job cannot be combined with the job of interest are written in a predetermined memory area or the like (step S2005). Note that at least one of setup item
10 values, which cannot be changed after a job is generated (e.g., the designated resolution, the number of bits per pixel, graphic mode, or the like), of the job that cannot be combined with the job of interest is different from that of the job of interest.

15 Finally, the job list is displayed in step S2006. In this case, as for the job for which the effect and reason why it cannot be combined with the job of interest are set in step S2005, a symbol indicating that this job cannot be combined with the job of
20 interest and a reason therefor are displayed in the column where that job is displayed. Fig. 26 shows this state. Since a job 2602 can be combined with a selected job 2601, but a job 2603 and subsequent jobs cannot be combined, symbols indicating that message are
25 displayed on the left side of document names, and

reasons why these jobs cannot be combined are displayed in a comment field.

On the other hand, if a plurality of jobs are selected, it is checked in step S2007 if the selected
5 jobs can be combined. If YES in step S2007, a combine button (a button 1606 in Fig. 16) is enabled (selectable) in step S2008, and the flow advances to step S2006 to display the job list.

If all the selected jobs cannot be combined, a
10 message indicating that all the held jobs cannot be combined is set in step S2009. In step S2006, symbols and comments are displayed for the jobs for which the message indicating that they cannot be combined is set in step S2009.

15 In this way, the job list is displayed. As described above, since the sequence in Fig. 20 is executed every time a job is selected from the job list, jobs that can be combined with the selected job, and possibility of the edit or combine operation for the
20 selected job can be presented to the user.

<Edit/combine Operation>

When the edit button (for a case wherein only one job is selected) or the combine button (for a case wherein a plurality of jobs are selected) is pressed
25 while a job or jobs are selected from the display job list, the sequence shown in Fig. 21 is executed. When

jobs which cannot be combined are selected, no combine operation is available.

It is checked in step S2101 if the combine operation is made. If YES in step S2101, selected job
5 output setup files are tentatively combined in step S2102. Since this operation is not settled, a tentative job output file is generated and used. Upon combining jobs, some setup values are changed to common values in place of the individual setups of the jobs.

10 As the method of setting common setups, the setup values may be changed to predetermined ones, or the setups of jobs other than the first job are set or cleared in correspondence with those of the first job. For example, the print methods of jobs to be combined
15 are commonly set to be one-sided print unless they are all designated with two-sided print. Also, the setup values of the binding margin, staple designation, ascending/descending print order, face-up/down print, use of an inserter, and the like are set in
20 correspondence with those of the first job. In addition, the setup values of the number of copies, bookbinding designation, and the like are cleared.

Preview display is executed using the job output setup file combined in step S2102 or that of a job
25 selected as a job to be edited in step S2103, and a target job list is displayed in step S2104. The

preview window displays thumbnail images of all pages contained in jobs to be edited or combined in accordance with their layouts. On the other hand, the target job list displays the names, number of pages, and page layouts of jobs to be edited or combined. In this list display, in case of the combine operation, the job order can be sorted desirably, and a desired job can be deleted from the target jobs. When the target job is operated in this manner, the sequence shown in Fig. 21 is executed again, and the preview window and target job list are re-displayed.

Also, the print setups of the target job can be changed. Items that can be changed are those which can be changed by editing the job output setup file. Items that require operations of intermediate data are inhibited from being operated in this embodiment. However, all items may be re-set regardless of the processing time or resources required. Items that can be re-set in the system of this embodiment are the print method (one-sided/two-sided/bookbinding), the number of copies, the presence/absence of staple, and the like.

<Print Preview Display of Target Job>

Fig. 22 is a flow chart showing the sequence for displaying the job preview window shown in Fig. 18 when the user instructs desired operation such as job edit,

combine, or the like on the list display window of print jobs shown in Fig. 16, and shows details of step S2103 in Fig. 21.

Referring to Fig. 22, the layout setups of target jobs are acquired in step S2201. The layout setup items include the print method, page layout, page frame, finishing, paper feed switching, and the like, and these pieces of information are acquired from the job output setup file shown in Figs. 10 to 13.

The layout setup items will be briefly explained below. Examples of items to be set are as follows.

(1) Print method: One of one-sided/two-sided/bookbinding is designated. The one- and two-sided print processes are well known. The bookbinding print process is a method of printing data to obtain the format of a book by only folding printed sheets once and binding them. When the bookbinding print mode is designated, one of a method of folding a set of copies once, and a method of designating a predetermined number of sheets, folding each predetermined number of sheets once, and then stacking and binding them can be designated. Such twofold unit is called a bookbinding unit.

In the bookbinding print process, since a stack of a designated number of sheets, e.g., two output sheets are bound by being folded once, data cannot be

printed in the order of logical pages created by the application. The output order of logical pages, i.e., the layout order of logical pages on physical pages, is determined in advance so that logical pages are

5 allocated in turn by turning pages of the bound sheets from the right to left (this direction is designated separately). Also, the order of logical pages differs depending on whether sheets are exhausted facing up or down.

10 Since the bookbinding print process corresponds to a two-sided 2-up print process in consideration of only the format regardless of the order of pages, four logical pages are printed on the obverse and reverse surfaces of a single sheet. Hence, the required number
15 S of sheets is given by $S = \text{the number of logical pages} / 4$ (with raising decimals to the next whole number). For example, when the exhaust method is face-up, and the bookbinding unit is S sheets, the $(4 \times (P - 1) + 2 \times Q - 1)$ -th logical page and $(4 \times (P - 1) + 4 \times S - 2 \times (Q - 1))$ -th logical page are laid out on
20 the obverse surface (the surface printed first) of the Q-th sheet of the P-th bookbinding unit, and the $(4 \times (P - 1) + 2 \times Q)$ -th logical page and $(4 \times (P - 1) + 4 \times S - 2 \times Q - 1)$ -th logical pages are laid out on the
25 reverse surface thereof. In case of the face-down

exhaust method, the reverse surface can replace the obverse surface.

(2) Book Opening Direction: This item indicates a direction to turn pages, and one of top open, right open, and left open can be designated.

(3) Bookbinding Unit: As described above, this item indicates a twofold unit in the bookbinding print process.

(4) Page Layout: One of a layout, so-called N-up print, that lays out N logical pages on one surface of a sheet (one physical page), and a layout, so-called poster print, that prints one logical page while dividing it onto a plurality of sheets can be designated.

(5) Finishing: This item can designate a process after the print process. For example, an external apparatus called an inserter can insert a sheet supplied independently of printed sheets as a cover page.

(6) Paper Source Switching: This item designates the way sheets are fed. For example, when middle insert is designated, sheets fed from one of feed ports undergo a print process, and sheets fed from the other feed port are inserted and exhausted between neighboring printed sheets. That is, sheets are alternately fed from the two feed ports.

The items that can be designated as layout setups have been explained.

In step S2202, the logical page information is acquired. The logical page is a page in data created
5 by the application program or the like. When the Nup print process is designated, a plurality of logical pages are printed on one physical page, i.e., on one surface of one sheet. This logical page information is as shown in Fig. 14.

10 In step S2203, a page template is rendered on the basis of the information acquired in steps S2201 and S2202. The page template is a framework of each physical page in accordance with the designated layout, and is rendered in correspondence with the designated
15 paper size and layout setups such as designation of one-sided/two-sided/bookbinding, portrait/landscape, and the like. However, when the poster print process is designated, since the combined state of images is displayed as a preview image, the above process is not
20 applied.

In step S2204, a page number given to each page to be displayed as a preview image is rendered. In this case, pages are given in the order of logical or physical pages in accordance with the layout. In this
25 way, the user can confirm accurate page numbers corresponding to the layout on the print preview window.

In step S2205, logical pages are rendered in correspondence with each page template. In this case, the job output setup file shown in Figs. 10 to 14 is looked up, and logical pages are rendered on a single physical page in accordance with the setups registered in the job output setup file. Intermediate data of the logical pages to be rendered are acquired with reference to the logical page information shown in Fig. 14.

Finally, in step S2206, the total number of pages or the required number of sheets is rendered. The total number of pages amounts to the number of logical pages, and the required number of sheets is the number of paper sheets to be output.

(Page Template Rendering)

Fig. 23 is a flow chart showing details of step S2203 in Fig. 22. The layout setups are acquired in step S2301 (enclosed in parentheses since the layout has already been acquired in step S2201 in Fig. 22), and the print method is checked in steps S2302 and S2303. If the bookbinding print process is selected, a page template for bookbinding print is acquired in step S2304; if the two-sided print process is selected, a page template for two-sided print is acquired in step S2309.

If the one-sided print process is selected, it is checked in step S2306 if the middle insert print process is selected. The middle insert print process is a print method for inserting and exhausting
5 independently fed paper sheets between neighboring output printed sheets, and is used when transparent documents for an overhead projector are printed. If the middle insert print process is selected, a page template for middle insert print is acquired in step
10 S2207; otherwise, a page template for one-sided print is acquired in step S2308.

Lastly, in step S2305 the page template is rendered in accordance with the acquired page template data.

15 (Page Number Rendering)

Fig. 24 is a flow chart showing details of step S2204 in Fig. 22. The layout setups are acquired in step S2401 (enclosed in parentheses since the layout has already been acquired in step S2201 in Fig. 22),
20 and the print method is checked in steps S2402 and S2403. If the bookbinding print process is selected, page numbers for bookbinding print are rendered in step S2404; if the two-sided print process is selected, page numbers for two-sided print are printed in step S2406.
25 On the other hand, if the one-sided print process is

selected, page numbers for one-sided print are rendered in step S2405.

(Logical Page Rendering)

Fig. 25 is a flow chart showing details of step S2205 in Fig. 22. The layout setups are acquired in step S2501 (enclosed in parentheses since the layout has already been acquired in step S2201 in Fig. 22), and the print method is checked in steps S2502 and S2503. If the bookbinding print process is selected, logical pages for bookbinding print are rendered in step S2504; if the two-sided print process is selected, logical pages for two-sided print are printed in step S2506. On the other hand, if the one-sided print process is selected, logical pages for one-sided print are rendered in step S2505. Since logical pages are rendered in accordance with the job output setup file and logical page information, a process that does not classify according to the print method may be done.

<Details of Page Template Rendering>

Fig. 27 is a flow chart showing details of the page template rendering process in step S2305 in Fig. 23. In step S2305, the process for rendering the acquired page template is executed.

In step S2701, the vertical dimensions of individual physical pages in the job are compared to search for a page with the largest vertical size. In

this case, the job searched is a print job to be edited when the user instructs to edit the stored job or is all print jobs to be combined when the user instructs to combine job. This search is made by looking up
5 physical page information from the output job setup file in Fig. 10 and comparing their vertical sizes. Note that data to be compared are physical pages which reflect the actual output sheet sizes and are rendered as page templates.

10 If a page with the maximum vertical size is found from all jobs to be compared, the templates of the individual pages to be displayed as preview images, which are acquired in steps S2307 to S2309 in Fig. 23 are rendered in a reduced scale, so that the template
15 of the page with the maximum vertical size found in step S2702 falls within the display frame of the preview display. Note that the templates of the individual pages are reduced at the same ratio to maintain the relative size relationship and the
20 vertical and horizontal directions. For example, when the job of interest includes a page with an A4 portrait size and a page with an A3 portrait size, the page template of the page with the A3 portrait size is reduced to fall within the preview display frame in the
25 vertical direction. On the other hand, the page with the A4 portrait size is reduced at the same reduction

ratio as the A3 size so that the size relationship is maintained, i.e., the length and width of the page with the A4 portrait size respectively become 1/2 those of the page with the A3 portrait size.

5 In this manner, since all pages fall within the preview window, the preview display window need not be scrolled, thus implementing display which is very easy to see. In addition, the relative size relationship can be expressed on the preview display. Since size
10 reduction is made to make the maximum page fall within the frame, the respective pages can be prevented from being excessively reduced, thus allowing display which is easy to see.

 Furthermore, every time a job list is edited or a
15 page is deleted from the preview window, the edit/combine process shown in Fig. 21 is re-executed, and the preview display process in Fig. 22 is re-executed accordingly. Hence, since the process in Fig. 27 is re-executed every time the aforementioned
20 processes are re-executed, preview display is made to always display a page with the maximum vertical size in the largest scale.

 Fig. 28 shows an example of preview display. Since "edit" of a job 2801 is designated, four pages
25 included in the print job 2801 are displayed on a preview display window 2802. The pages displayed are

four physical pages respectively having a letter size, A4 landscape size, a 11 x 17 size, and a B4 landscape size. Upon making this display, the template sizes are reduced or enlarged in the sequence shown in Fig. 27.

5 An explanation will be given along Fig. 27. That is, as a result of comparison of the vertical dimensions of all pages, the page having the 11 x 17 size has the maximum vertical size. Hence, the template of the 11 x 17 size is zoomed to just fall within the display
10 window 2802, and the remaining templates of the letter size, A4 size, and B4 size are zoomed to have the same ratio of sizes relative to the page of the 11 x 17 size as that of actual paper sheets. After that, these templates are rendered and displayed.

15 When the user points to a page displayed as a preview image using a pointer or the like, the size of the pointed page is displayed. In Fig. 28, the fourth page at the right end is pointed, and "B4" is displayed as its size.

20 When the user selects the third page as that having the maximum size from the state in Fig. 28 and presses a "DELETE" button 2804 in Fig. 28 to instruct "delete", the third page is deleted, and the preview window is updated, thus deleting the third page from
25 the preview window. Fig. 29 shows this state. When the first, second, and fourth pages are searched for a

page with the maximum vertical dimension after the third page is deleted, the first page with the letter size has the maximum vertical dimension. Hence, the templates are zoomed so that the page with the letter size falls within the preview display window, and other pages are zoomed at the same ratio as the page with the letter size in the sequence shown in Fig. 27. As a result, the page with the letter size is displayed to just fall within the display window, as shown in Fig. 29.

As described above, upon displaying a preview image of a document including pages (paper sheets) of various sizes and directions, since page templates are zoomed so that a page with the maximum vertical size just falls within the preview window, the display space can be efficiently used. Also, since pages are juxtaposed and displayed, all pages can be previewed by only horizontally scrolling the window. Also, since other pages are zoomed at the same ratio as the maximum page, relative page sizes can be visually recognized on the preview display window. Also, by displaying the size of the designated page, the user can recognize not only relative sizes but also the actual size.

Note that the present invention may be applied to either a system constituted by a plurality of devices (e.g., a host computer, an interface device, a reader,

a printer, and the like), or an apparatus consisting of a single equipment (e.g., a copying machine, a facsimile apparatus, or the like).

The objects of the present invention are also
5 achieved by supplying a storage medium, which records a program code that can implement the functions of the above-mentioned embodiments, i.e., the sequences shown in Figs. 19 to 25 and Fig. 27 to the system or apparatus, and reading out and executing the program
10 code stored in the storage medium by a computer (or a CPU or MPU) of the system or apparatus.

In this case, the program code itself read out from the storage medium implements the functions of the above-mentioned embodiments, and the storage medium
15 which stores the program code constitutes the present invention.

As the storage medium for supplying the program code, for example, a floppy disk, hard disk, optical disk, magneto-optical disk, CD-ROM, CD-R, magnetic tape,
20 nonvolatile memory card, ROM, and the like may be used.

The functions of the above-mentioned embodiments may be implemented not only by executing the readout program code by the computer but also by some or all of actual processing operations executed by an OS
25 (operating system) running on the computer on the basis of an instruction of the program code.

Furthermore, the functions of the above-mentioned
embodiments may be implemented by some or all of actual
processing operations executed by a CPU or the like
arranged in a function extension board or a function
5 extension unit, which is inserted in or connected to
the computer, after the program code read out from the
storage medium is written in a memory of the extension
board or unit.

As described above, print preview display that
10 reflects the layout to be printed as faithfully as
possible and is most easy to see without requiring the
user to designate the layout for preview display can be
made.

When a preview image of a document including
15 pages with various sizes and directions is to be
displayed, these pages are displayed as preview images
so that a page with the maximum vertical size just
falls within the preview display window, thus
efficiently using the display space. Hence, all pages
20 can be previewed by horizontally scrolling the display
window. Also, since all the pages are zoomed at the
same ratio as that of the maximum page, relative page
sizes can be visually recognized on the preview display
window. By displaying the size of the designated page,
25 the user can recognize not only relative sizes but also
the actual size.

As many apparently widely different embodiments
of the present invention can be made without departing
from the spirit and scope thereof, it is to be
understood that the invention is not limited to the
5 specific embodiments thereof except as defined in the
appended claims.

WHAT IS CLAIMED IS:

1. A print control method comprising the step of:
searching pages included in a print job for a
page with a maximum size;
5 zooming all pages included in the print job in a
scale at which the page with the maximum size falls
within a predetermined frame; and
displaying preview images of all the zoomed pages.
2. The method according to claim 1, wherein when a
10 page is deleted from the stored print job, pages
included in the print job are searched again for a page
with a maximum size, and all pages included in the
print job are displayed as preview images in a scale at
which the page with the maximum size falls within the
15 frame.
3. The method according to claim 1, wherein the
scale at which the page with the maximum size falls
within the frame is a scale at which a vertical
dimension of the page with the maximum size becomes
20 smaller than a vertical dimension of the frame.
4. The method according to claim 1, wherein when a
page displayed within the frame is designated, a size
of the designated page is displayed.
5. The method according to claim 1, further
25 comprising a step of printing the stored print job.

6. The method according to claim 1, further comprising a storage step of storing print data in units of print jobs.

7. A print control apparatus comprising:

5 a searcher arranged to searching pages included in a print job for a page with a maximum size;

a zoommer arranged to zoom all pages included in the print job in a scale at which the page with the maximum size falls within a predetermined frame; and

10 a display they displays preview images of all the zoomed pages.

8. The apparatus according to claim 7, wherein when a page is deleted from the stored print job, pages included in the print job are searched again for a page
15 with a maximum size, and all pages included in the print job are displayed as preview images in a scale at which the page with the maximum size falls within the frame.

9. The apparatus according to claim 7, wherein the
20 scale at which the page with the maximum size falls within the frame is a scale at which a vertical dimension of the page with the maximum size becomes smaller than a vertical dimension of the frame.

10. The apparatus according to claim 7, wherein when
25 a page displayed within the frame is designated, a size of the designated page is displayed.

11. The apparatus according to claim 7, further comprising a printer that prints the stored print job.

12. The apparatus according to claim 7, further comprising storage that stores print data in units of
5 print jobs.

13. A computer readable storage medium that stores a computer program for making a computer display pages included in a stored print job within a predetermined frame, said program including:

10 a code for searching pages included in a print job for a page with a maximum size;

a code for zooming all pages included in the print job in a scale at which the page with the maximum size falls within a predetermined frame; and

15 a code for displaying preview images of all the zoomed pages.

14. The medium according to claim 13, wherein when a page is deleted from the stored print job, said computer program searches pages included in the print
20 job again for a page with a maximum size, and displays as preview images all pages included in the print job in a scale at which the page with the maximum size falls within the frame.

15. The medium according to claim 13, wherein the
25 scale at which the page with the maximum size falls within the frame is a scale at which a vertical

dimension of the page with the maximum size becomes smaller than a vertical dimension of the frame.

16. The medium according to claim 13, wherein when a page displayed within the frame is designated, said
5 computer program displays a size of the designated page.

17. The medium according to claim 13, wherein said computer program further includes a code for printing the stored print job.

18. The medium according to claim 13, wherein said
10 computer program further includes a code for storing print data in units of print jobs.

ABSTRACT OF THE DISCLOSURE

When "store" of intermediate data is designated in a print process, a spooler stores intermediate data and an output job setup file in a spool file. When the stored job is selected, a previewer displays a list of jobs, and displays a print preview image. In this case, pages are displayed so that a page with the maximum size just falls within a display window, and other pages are displayed in the same scale as that of the maximum page.


FIG. 1

FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6





FIG. 7

FIG. 8

PROPERTIES OF Canon LASER SHOT LBP-720

?

X

GENERAL

DETAILS

MAIN

PAPER

LAYOUT

DEVICE OPTION

OVERLAY

PAPER SIZE(Z):

A4

OUTPUT PAPER(Q):

A4

ENLARGEMENT/REDUCTION RATIO(E):

PAGE LAYOUT:

NUMBER OF PAGES(U):

PRINT ORDER(I):

TWO-PAGE PRINT

FROM LEFT TO RIGHT

PRINT DIRECTION:

A

PORTRAIT(E)

A

LANDSCAPE(L)

PAPER SOURCE(S):

AUTO

NUMBER OF COPIES(C):

1

MORE OPTIONS(M)...

RESTORE DEFAULTS(D)

OK

CANCEL

APPLY(A)

HELP

FIG. 9

901

PROPERTIES OF Canon LASER SHOT LBP-720

GENERAL DETAILS PAGE SETUP FINISHING PAPER FEED PRINT PRINT QUALITY DEVICE SETUP

FAVORITE(E): [DEFAULT SETUP] [STORE] [PRINT] [A4 STORE PREVIEW] [DQ MAILBOX]

DOCUMENT SIZE(S): [A4] [STORE PREVIEW] [DQ MAILBOX]

OUTPUT PAPER SIZE(Z): [A4] [STORE PREVIEW] [DQ MAILBOX]

NUMBER OF COPIES(C): [1] COPIES(1~255)

PRINT DIRECTION(I): [A] ☒ PORTRAIT [O] LANDSCAPE

PAGE LAYOUT(L): [1 PAGE/SHEET(DEFAULT)]

☐ DESIGNATE MAGNIFICATION(M): [100] % (50~200)

☐ STAMP(W): [CONFIDENTIAL]

CONFIRM SETUP(V) [EDIT STAMP(I)...]

USER-DEFINED PAPER(U)... [PAGE OPTIONS(N)...] [RESTORE DEFAULTS(R)]

OK CANCEL APPLY(A) HELP

FIG. 10

ID WHICH CAN IDENTIFY JOB	~1001
JOB SETUP INFORMATION	~1002
NUMBER OF PHYSICAL PAGES OF JOB	~1003
FIRST PHYSICAL PAGE INFORMATION	~1004
SECOND PHYSICAL PAGE INFORMATION	~1005
.....	~1006
LAST PHYSICAL PAGE INFORMATION	~1007

FIG. 11

TOTAL NUMBER OF PHYSICAL PAGES	~1101
TOTAL NUMBER OF LOGICAL PAGES	~1102
NUMBER OF COPIES	~1103
COPY SET PRINT	~1104
FINISHING INFORMATION	~1105
ADDITIONAL PRINT INFORMATION	~1106

FIG. 12

PHYSICAL PAGE NUMBER	~ 1201
PHYSICAL PAGE SETUP INFORMATION	~ 1202
NUMBER n OF LOGICAL PAGES ASSIGNED PER PHYSICAL PAGE	~ 1203
FIRST LOGICAL PAGE INFORMATION	~ 1204
SECOND LOGICAL PAGE INFORMATION	~ 1205
.....	~ 1206
n-TH LOGICAL PAGE INFORMATION	~ 1207

FIG. 13




FIG. 14





FIG. 15

FIG. 16




FIG. 17




FIG. 18

?

X

JOB EDIT

COMBINED JOB NAME

Microsoft Word-EMPLOYEE MAGAZINE(SHANAIHOU) pr.doc

TOTAL PAGES:2

1

2

DELETE PAGE

PREVIEW

TARGET JOB LIST

PRINT SETUP

NUMBER OF COPIES(C):

1

COPIES(1-255)

PRINT METHOD:

ONE-SIDED PRINT

STAPLE

SADDLE STITCHING(I):

APPLY COMMON LAYOUT

1 PAGE/SHEET

PAGE LAYOUT(L):

LAYOUT ORDER(X):

JOB BOUNDARY SETUP:

1801

MORE OPTIONS...

1802

RESTORE DEFAULTS

OK

CANCEL

HELP


FIG. 19

FIG. 20





FIG. 21


FIG. 22

FIG. 23




FIG. 24




FIG. 25





FIG. 26



2601

2602

2603


FIG. 27

FIG. 28




FIG. 29

EDIT JOB SETTINGS

NAME COMBINED DOCUMENTS

Microsoft Word-Document2

TOTAL PAGES:3

PAGE 1 (LETTER)
LETTER

PAGE 2 (A4)

PAGE 4 (B4)

123

DELETE

PRINT PREVIEW

JOB LISTPRINT SETTINGS

DOCUMENT NAME

IMPRESSION COUNT

PAGE LAYOUT

Microsoft Word-Document2

3

1 PAGE PER SH

DELETED FROM LIST

RESTORE DEFAULTS

OK

CANCEL

HELP